
 <b>TI8100en</b>	<b>Technical Information</b>	
<b>CRW9-Series (H&amp;T)</b>	<b>Room Humidity and Temperature Sensor with BACnet or Modbus RTU communication</b>	

The CRW9- Series (H&T) is designed to measure temperature, relative humidity,

absolute humidity, enthalpy or dew point in rooms or areas

The sensor operates with low power supply

BACnet MSTP and Modbus RTU on Board

The sensor output is BACnet MSTP / Modbus RTU communication (RS485)



#### USE

- In Building Automation System where BACnet MSTP or MODBUS RTU communication protocols are used
- Compatible to all common HVAC DDC and Analog Controls systems, with Building Automation System
- Relative humidity, absolute humidity, enthalpy or dew point and temperature measurement in rooms and areas
- Used in all common HVAC applications
- Used in Commercial and Industrial Buildings

#### Features

- BACnet / MODBUS address setting over BUS protocol
- High Humidity accuracy
- Modern and practical product design
- Easy to use, install and maintain

#### Product Range

Order Codes	Power Supply	Communication system	Humidity Measuring	Measuring Units	IP Rating
CRW9.AA	AC/DC 24V (±10%)	BACnet MSTP (RS485)	rel. humidity	0...100%	Housing IP20  Sensing Element IP67
			absolute humidity	0...50gr/m3	
CRW9.AG		Modbus RTU (RS485)	dew point	-20....80°C	
			enthalpy	0...85kJ/Kg	

Sensor Specification	Sensor Specification	Measured	Temperature & Humidity	
		Outputs	BACnet MSTP or Modbus RTU communication, RS485	
		Accuracy	relative humidity	± 2% over measuring range
			absolute humidity	± 2% over measuring range
			enthalpy	± 2% over measuring range
			dew point	± 2% over measuring range
			Temperature	see chart, page 4
		IP- Rating sensor element	IP67 to IEC60529	
		Repeatability (H)	±0.1C ; ±0.1% r.h.	
		Long Term Drift (H)	< 0.04C / year ; < 0.5% r.h. / year	
		Measuring Range (H)	see charts page 4	
		Measuring Range (T)	-40°C...120°C	
Technical Information	Electrical Information	Power Supply	AC/DC 24V (±10%)	
		Frequency	50 / 60 Hz at AC 24V	
		Terminal Clamp	Screw terminal, max. 1.5mm²	
		Power Consumption	≤ 1W @ AC 24V / DC 24V	
	Mechanical Information	Cable Entry	30x15mm, on the backside of the housing	
		Sensing Element Position	Inside the housing, bottom of the housing	
	Color and Materials	Housing Cover	White ABS, RAL9001 (Cream White)	
		Housing Bottom	White ABS, RAL9001 (Cream White)	
	Environmental Conditions	Operation Temperature	-25°C...+70°C	
		Operation Humidity	<85% r.h., no condensation	
		Transport Temperature	-35°C...+70°C	
		Transport Humidity	< 90% r.h.	
		Storage Temperature	-10°C...+70°C	
		Storage Humidity	< 85% r.h., no condensation	
	Norms and Directives	IP- Rating	IP20 to IEC60529	
		Safety Class	III to EN 60 730	
		Product Standard 1	Automatic Electric. Controls for household and similar use	
		Product Standard 2	2009/EN 60 730-1	
		CE Conformities to	2004/108/EG Electromagnetic Compatibility EMV	
		CE Electromagnetic Compatibility Emitted Interference	2000/EN60730-1 Emitted Interference	
		CE Electromagnetic Compatibility Interference resistance	2000/EN60730-1 Interference Resistance	
		RoHS Compatibility	RoHS 2011/65/EC	
		Operation Climatic Condition	IEC 60 721-3-3	
		Operation Mechanical Condition	IEC 60 721-3-2 to class2M2	
		Transport to Climatic Condition	IEC 60 721-3-2	
		Transport Mechanical Condition	IEC 60 721-3-2 to class2M2	
		Storage Climatic Condition	IEC 60 721-3-1	
		Storage Mechanical Condition	IEC 60 721-3-1 to class2M2	
	Miscellaneous	Accessories	Accessory not included in delivery	TRA0.A (106mmx106mm backplate)
		Shipping & Handling	Minimum Order	1 box with 1 piece
Package Material			Rigid Cardboards	
Order Notes		Order Code	see product range page 1, e.g. CRW9.AA	

Modbus Parameters	Address Number		Register Description	
	4		Software Version	actual version
	6		Modbus Address	Default 254, selectable 1...254
	8		Hardware Version	actual version
	10		Protocol	0= MODBUS RTU ; 1= BACnet MSTP
	11		Baud Rate autodetection	0= OFF ; 1= On
	15		Baud Rate, (if autodetection is OFF)	0= 9600 ; 1= 19.200 ; 2= 38.400 ; 3= 57.600 ; 4= 115.200
	34		Temperature, digital	actual value
	35		Rel. Humidity	actual value
	41		Dew Point Value, actual	actual value
	42		Enthalpy Value, actual	actual value
	44		Absolute Humidity, actual	actual value
	45		Temperature, passive	actual value
BACnet Parameters	Supported BACnet Objects Types			
			analog-value	
			device	
	Supported BACnet Services			
			who-is	
			i-am	
	object-identifier, object-name, object-type, present-value, units, object-list, vendor-id, vendor-name, system-status, confirmed-service, unconfirmed-services			
	MSTP Objects			
			analog-value	
			BACnet Address	Default 127, selectable 0...127
	AV0		Baud rate autodetection	default 0, 0= OFF ; 1= ON
	AV1		Baud Rate, (if autodetection is OFF)	0= 9600 ; 1= 19.200 ; 2= 38.400 ; 3= 57.600 ; 4= 115.200
	AV2		Humidity Mode	0= Dew Point ; 1= Enthalpy ; 2= Absolute Humidity ; 3= relative humidity
	AV3		Protocol	0= Modbus ; 1= BACnet
	AV4		Temperature	actual value (-40...120°C)
	AV6		Relative Humidity	actual value (0...100% rel. Humidity)
	AV7		Absolute Humidity	actual value (0...50gr/m³)
	AV8		Dew Point	actual value (-20...80°C)
	AV9		Enthalpy	actual value (0...85kJ/kg)
			Device	
			device-identifier	
			device-name	
The function "Baud Rate autodetection" can only be used during the product is been setup. When the product is working with the BAS, the "Baud Rate autodetection" has to be set to 0= OFF and the actual Baud Rate has to be set.				
<div> <div>Thermokon Asia Pacific</div> <div> All Information and technical data are subject to alteration </div> <div>CRW9- Series (T) V20.1</div> <div>Page 3/4</div> </div>				

